

Technical Specifications:

Brand	Name:	BACBON	
Model No:		FC-400	
Country of Origin:		China	
	Features		
a)	All in one 4K	UHD Camera and Audio speaker makes group video calls easier and more	
		ering exceptional audio and video quality for enterprises. It is also equipped wit	
	cutting-edge f	eatures like Smart Frame, Smart Speaker, True WDR, and FOV 120° to upgrade.	
b)	Auto-framing	, minimum 5X digital zoom,120° Viewing angle,12MP, 3 Camera position presets	
c)	automatically	frames all meeting participants, adjusting the camera zoom, pan, and focus to fit	
	everyone on-s	creen in seconds without overreacting to unimportant movement.	
d)		Instantly Identifies Speakers-	
e)		ve Smart Speaker Tracking pinpoints speakers wherever they are in the room,	
	0 0	h noise to zoom in on the human voice. Also, Smart Speaker's 8 to 10-meter	
	-	up range saves wasted time moving speakers closer to the microphone.	
f)		n the Room Camera captures the room with a 120° FOV multi-glass lens that	
	features a motorized 180° pan and 105° tilt view for a wider perspective than ever. No more		
,		where your seat is located.	
g)		d video conferencing applications – such as Zoom Rooms, Microsoft Teams	
		hers – directly on the All-in-One Digital Smart Board with no computer or lapto	
1 \	required.		
h)		nan perception, and motorized PTZ, Auto-level loud and soft voices – while	
		nwanted noise – with AI-based Right Sound [™] technology that improves over	
Voort	time.	ting participants with AI Viewfinder which uses scope awareness to entimize	
-		eting participants with AI Viewfinder, which uses scene awareness to optimize ng and camera control.	
	a sensor:		
		ge supports up to 4K	
	nch CMOS,12PI		
	ng Mode: Progr		
FOV 12	0		
	nge UP 15°, dov	vn 15°,	
	ength Fixed		
	0	080p, 720p, 960 x 540, 848 x 480, 800 x448, 640 x 480, 640 x 360, 424 x 240, 320 x 24	
	80 at 60, 30, 15 f		
Minim	al Focusing Illu	mination : <u>0.05Lux@f/2.4,AGC</u> ON	
White I	Balance: Auto		
Digital	Noise Reeduca	tion 2D & 3D Digital Noise reduction	
SmartF	rame SmartS p	eaker Automatic FOV adjustment (auto	
focus)	to fit all particip	pants and focus on the speaker	
120 w i	de field of view	7	
Digital	zoom rate up t	o minimum 5X leveraging 4K sensor	
Feature	e : EPTZ, Auto-	Framing	
Sound	System		
		ume Level (dBSPL) : 86dBSPL@1m,1kHZ	
Freque		dB) –150Hz-15kHz	



House # 13(5th Floor), Block-C, Main Road, Banasree, Rampura, Dhaka-1219, Bangladesh

0	Signal to Noise Ratio >75dB			
e e	Speaker Channel: 1			
(Output Power 1x8W			
5	Filt: Total vertical viewing area 105.			
]	Microphone System			
1	Min: Microphones 6 array directional microphones supporting Minimum 8 m			
]	Pickup.			
8	3W stereo full range speakers with professional bass port			
t	uned for communication.			
1	Volume up to 96 dB SPL at 1/2 meter.			
]	Echo cancellation.			
]	Noise suppression.			
	Operating System USB			
(Operating System: Windows 10 or upper version			
	Color System: H.264/YUY2MJPG			
1	USB Video Communicate Protocol: UVC2.			
]	Input/output Interface			
]	Line in/Out: 1x3.5mm earphone pot			
	HDMI: 1xHDMI1.4			
]	nternet Connection: Ethernet:1xRJ45(10/100Mbps). Wi-Fi-2.4G/5G Dual Brand Wi-Fi			
1	USB Interface Min: 1xUSB3.0Type A			
1	DC in: 1xDC2.0			
	Camera Control			
]	R remote control.			
1	VISCA/pelco P/pelco D via RS232.			
1	UVC /UVA plug and plan.			
]	PTZ App			
]	Power Supply			
	AC 100V~ 240V, 50/60 Hz.			
]	input Voltage: 12V			
]	Power Consumption (Typ) :36W			
(Current Consumption :3A			
]	Environmental Data			
	Operation temperature: 0 °C ~40°C.			
	Operation humidity: 20%20%~.			
	Storage temperature: 20 °C ~60°C.			
	Storage humidity: 20%20%~			
_	Dimensions			
	Package dimensions: 739 x 193 x 229 mm.			
	Package weight: 4.16 kg/9.3 lbs.			
	Camera: 650 x 100 x 109.5 mm/2.133 kg			
	Remote control: 200 x 50 x 2 1 mm /0.09 kg			
	Camera Support Compatible Applications			
	Zoom, Microsoft® T eams, Skype for Business, Skype			
	Google Hangout s Intel® Unite™, RingCentral, BlueJeans,			
	Microsoft® Lync™, Vidyo, vMix, WebRTC, Wirecast, XSplit			
	Warranty: 3 Years warranty			